

Verbatim LED Recessed Downlight INDIRECT 220mm 20W/30W 3000K 1650lm/2450lm 40° White

- Beautiful, indirect light
- Minimum glare (UGR<13) and high visual comfort
- 70,000 hours lifetime (L80B10)
- Light output of 1650/2450lm
- 3000K warm white light
- 40° beam angle
- DALI option available
- Narrow binning of SDCM ≤3
- 5 Years Warranty

Product Number 52510

General Data

Installation type	Recessed
Housing material	Aluminium & PBT
Housing colour	white - RAL9003
Protection class	IP40
Dimmable	Yes with optional DALI driver

Geometric Data

Height (mm)	121
Outer diameter (mm)	220
Inner diameter (mm)	205
Weight (g)	1150
Cut-out dimensions (mm)	205

Electric Data

Wattage (W)	20/30
Voltage (V)	220-240
Current (mA)	95/140
Power Factor	0.9
Operating Frequency (Hz)	50/60
Safety Class	Class III
Power supply	External

Photometric Data

Luminous Flux (lm)	1650/2450
CRI	80
CCT (K)	3000
Luminous Efficacy (lm/W)	83/82
Luminous Intensity (cd)	3400/5100
Beam Angle (°)	40
UGR	11.0 / 12.4

Lifespan

Lifetime (hrs)	70,000
Switching Cycle	100,000

Mechanical Parameters


Glow wire test	850°C
----------------	-------



Product image




Technical drawing



Application image



Energy Rating



Technical Packaging Details

Barcode

023942525103

EAN 128

(02)00023942525103(37)01(91)469

EAN 14

50023942525108

Pack Dimensions(HxWxL)

250 x 250 x 155 (mm)

Pack Weight

1314 (g)

MOQ

1

Cartons/Pallet

72

Layers/Pallet

6

Units/Pallet

72



Photometric Diagrams

